

TuffCut® AL / X-AL

135B / 138B Series Recommended Cutting Data - Profile Milling - Inch

If axial depth (ap) is less than the ball diameter, the speed is figured using the effective cutting diameter.

Workpiece Material Group	ISO	Coolant ● Preferred	Profile Milling (ae)*				End Mill Diameter (inch)									
							1/8*	3/16*	1/4*	5/16	3/8	1/2	5/8	3/4	1	
			10%	20%	30%	50%	ae > .3D use <1D ap ae < .2D use < 2D ap *Profile Milling at > 25% ap is not recommended for diameters 1/4" and below.									
			vc - SFM				← Multiply fz by this Factor based on ae. When finishing, use the standard fz per chart below. Only add chip thinning when roughing or semi-finishing.									
								fz - in/tooth								
Non-Ferrous - Aluminum / Aluminum Alloys < 10% Si	N	●	2000	1800	1200	900	.0010	.0018	.0025	.0030	.0037	.0050	.0065	.0075	.0100	
Non-Ferrous - Aluminum / Aluminum Alloys > 10% Si	N	●	1500	1200	1000	800	.0010	.0018	.0025	.0030	.0037	.0050	.0065	.0075	.0100	
Non-Ferrous - Brass	N	●	900	800	600	500	.0015	.0025	.0032	.0040	.0050	.0060	.0075	.0100	.0120	
Non-Ferrous - Cu/Cu Alloys / Magnesium	N	●	1000	800	600	500	.0015	.0025	.0032	.0040	.0050	.0060	.0075	.0100	.0120	
Non-Ferrous - Plastics	N	●	900	800	600	500	.0015	.0025	.0032	.0040	.0050	.0060	.0075	.0100	.0120	

Above 20,000 RPM, Tool Balancing Required.

135B / 138B Series Recommended Cutting Data - Profile Milling - Metric

If axial depth (ap) is less than the ball diameter, the speed is figured using the effective cutting diameter.

Workpiece Material Group	ISO	Coolant ● Preferred	Profile Milling (ae)*				End Mill Diameter (mm)							
							3*	5*	6*	8	10	14	16	
			10%	20%	30%	50%	ae > .3D use <1D ap ae < .2D use < 2D ap *Profile Milling at > 25% ap is not recommended for diameters 6mm and below.							
			vc - m/min				← Multiply fz by this Factor based on ae. When finishing, use the standard fz per chart below. Only add chip thinning when roughing or semi-finishing.							
								fz - mm/tooth						
Non-Ferrous - Aluminum / Aluminum Alloys < 10% Si	N	●	600	550	365	275	.0300	.0450	.0630	.0810	.0930	.1270	.1650	
Non-Ferrous Aluminum / Aluminum Alloys > 10% Si	N	●	450	365	305	250	.0300	.0450	.0630	.0810	.0930	.1270	.1650	
Non-Ferrous - Brass	N	●	275	250	180	150	.0450	.0630	.0810	.0810	.1270	.1650	.1900	
Non-Ferrous - Cu/Cu Alloys / Magnesium	N	●	300	250	180	150	.0450	.0630	.0810	.0810	.1270	.1650	.1900	
Non-Ferrous - Plastics	N	●	275	250	180	150	.0450	.0630	.0810	.0810	.1270	.1650	.1900	

Above 20,000 RPM, Tool Balancing Required.

Spindle Maximum - Should the calculated spindle speed be more than your actual spindle maximum, use this formula:
 (Calculated Feed x Spindle Maximum)/Calculated Speed.

Technical data provided should be considered advisory only as variations may be necessary depending on the particular application.

TuffCut® AL / X-AL

135B / 138B Series Recommended Cutting Data - Slotting - Inch

If axial depth (ap) is less than the ball diameter, the speed is figured using the effective cutting diameter.

Workpiece Material Group	ISO	Coolant • Preferred	Slotting*			End Mill Diameter (inch)								
						1/8*	3/16*	1/4*	5/16	3/8	1/2	5/8	3/4	1
			25%	50%	100%	*Slotting at > 25% ap is not recommended for diameters 1/4" and below.								
			vc - SFM			fz - in/tooth								
Non-Ferrous - Aluminum / Aluminum Alloys < 10% Si	N	•	2000	1500	1000	.001-.002	.004-.006	.004-.008	.005-.009	.007-.012	.010-.020	.015-.020	.015-.020	.015-.020
Non-Ferrous - Aluminum / Aluminum Alloys > 10% Si	N	•	1500	1200	800	.001-.002	.004-.006	.004-.008	.005-.009	.007-.012	.010-.020	.015-.020	.015-.020	.015-.020
Non-Ferrous - Brass	N	•	600	500	400	.001-.002	.004-.006	.004-.008	.005-.009	.007-.012	.010-.020	.015-.020	.015-.020	.015-.020
Non-Ferrous - Cu/Cu Alloys / Magnesium	N	•	500	400	300	.001-.002	.004-.006	.004-.008	.005-.009	.007-.012	.010-.020	.015-.020	.015-.020	.015-.020
Non-Ferrous/Plastics		•	1200	1000	800	.001-.002	.004-.006	.004-.008	.005-.009	.007-.012	.010-.020	.015-.020	.015-.020	.015-.020

Above 20,000 RPM, Tool Balancing Required.

135B / 138B Series Recommended Cutting Data - Slotting - Metric

If axial depth (ap) is less than the ball diameter, the speed is figured using the effective cutting diameter.

Workpiece Material Group	ISO	Coolant • Preferred	Slotting*			End Mill Diameter (mm)						
						3*	5*	6*	8	10	14	16
			25%	50%	100%	*Slotting at > 25% ap is not recommended for diameters 6mm and below.						
			vc - m/min			fz - mm/tooth						
Non-Ferrous - Aluminum / Aluminum Alloys < 10% Si	N	•	600	450	300	.076-.101	.101-.152	.101-.203	.152-.203	.177-.304	.254-.508	.381-.508
Non-Ferrous - Aluminum / Aluminum Alloys > 10% Si	N	•	450	365	250	.076-.101	.101-.152	.101-.203	.152-.203	.177-.304	.254-.508	.381-.508
Non-Ferrous - Brass	N	•	180	150	120	.076-.101	.101-.152	.101-.203	.152-.203	.177-.304	.254-.508	.381-.508
Non-Ferrous - Cu/Cu Alloys / Magnesium	N	•	150	120	90	.076-.101	.101-.152	.101-.203	.152-.203	.177-.304	.254-.508	.381-.508
Non-Ferrous - Plastics	N	•	365	300	250	.076-.101	.101-.152	.101-.203	.152-.203	.177-.304	.254-.508	.381-.508

Above 20,000 RPM, Tool Balancing Required.

Spindle Maximum - Should the calculated spindle speed be more than your actual spindle maximum, use this formula:
(Calculated Feed x Spindle Maximum)/Calculated Speed.

Technical data provided should be considered advisory only as variations may be necessary depending on the particular application.