


## TuffCut® XR - Series 177S



- Variable helix.

ALtima®		DC (h10)		DCONMS	DN	OAL	APMX	LU	RE	Shank
Tool No.	EDP	mm	Decimal	mm	mm	mm	mm	mm	Inch	
177S1181A	18218	3	.1181	6	2.9	50	5	11		DIN 6535 HA
177S1181R008A	18200	3	.1181	6	2.9	50	5	11	0.20	DIN 6535 HA
177S1181AW	18254	3	.1181	6	2.9	50	5	11		DIN 6535 HB
177S1181R008AW	18236	3	.1181	6	2.9	50	5	11	0.20	DIN 6535 HB
177S1575A	18220	4	.1575	6	3.9	50	6	14		DIN 6535 HA
177S1575R008A	18202	4	.1575	6	3.9	50	6	14	0.20	DIN 6535 HA
177S1575AW	18256	4	.1575	6	3.9	50	6	14		DIN 6535 HB
177S1575R008AW	18238	4	.1575	6	3.9	50	6	14	0.20	DIN 6535 HB
177S1969A	18222	5	.1968	6	4.9	57	8	17		DIN 6535 HA
177S1969R008A	18204	5	.1968	6	4.9	57	8	17	0.20	DIN 6535 HA
177S1969AW	18258	5	.1968	6	4.9	57	8	17		DIN 6535 HB
177S1969R008AW	18240	5	.1968	6	4.9	57	8	17	0.20	DIN 6535 HB
177S2362A	18224	6	.2362	6	5.8	57	9	20		DIN 6535 HA
177S2362R012A	18206	6	.2362	6	5.8	57	9	20	0.30	DIN 6535 HA
177S2362AW	18260	6	.2362	6	5.8	57	9	20		DIN 6535 HB
177S2362R012AW	18242	6	.2362	6	5.8	57	9	20	0.30	DIN 6535 HB
177S3150A	18226	8	.3150	8	7.6	63	12	26		DIN 6535 HA
177S3150R020A	18208	8	.3150	8	7.6	63	12	26	0.50	DIN 6535 HA
177S3150AW	18262	8	.3150	8	7.6	63	12	26		DIN 6535 HB
177S3150R020AW	18244	8	.3150	8	7.6	63	12	26	0.50	DIN 6535 HB
177S3937A	18228	10	.3937	10	9.6	72	15	32		DIN 6535 HA
177S3937R020A	18210	10	.3937	10	9.6	72	15	32	0.50	DIN 6535 HA
177S3937AW	18264	10	.3937	10	9.6	72	15	32		DIN 6535 HB
177S3937R020AW	18246	10	.3937	10	9.6	72	15	32	0.50	DIN 6535 HB
177S4724A	18230	12	.4724	12	11.4	83	18	38		DIN 6535 HA
177S4724R020A	18212	12	.4724	12	11.4	83	18	38	0.50	DIN 6535 HA
177S4724AW	18266	12	.4724	12	11.4	83	18	38		DIN 6535 HB
177S4724R020AW	18248	12	.4724	12	11.4	83	18	38	0.50	DIN 6535 HB
177S6299A	18232	16	.6299	16	15.2	98	24	50		DIN 6535 HA
177S6299R039A	18214	16	.6299	16	15.2	98	24	50	1.00	DIN 6535 HA
177S6299AW	18268	16	.6299	16	15.2	98	24	50		DIN 6535 HB
177S6299R039AW	18250	16	.6299	16	15.2	98	24	50	1.00	DIN 6535 HB
177S7874A	18234	20	.7874	20	19.2	112	30	62		DIN 6535 HA
177S7874R039A	18216	20	.7874	20	19.2	112	30	62	1.00	DIN 6535 HA
177S7874AW	18270	20	.7874	20	19.2	112	30	62		DIN 6535 HB
177S7874R039AW	18252	20	.7874	20	19.2	112	30	62	1.00	DIN 6535 HB

Metric (mm)	
DC	Tolerance (h10)
3.00	+0.00/-0.040
>3.00 - 6.00	+0.00/-0.048
>6.00 - 10.00	+0.00/-0.058
>10.00 - 18.00	+0.00/-0.070
>18.00 - 20.00	+0.00/-0.084

Metric (mm)	
DCONMS	Tolerance (h6)
6.0	+0/-0.008
6.01 - 10.0	+0/-0.009
10.01 - 18.0	+0/-0.011
18.01 - 20.0	+0/-0.013

Metric (mm)	
RE	Tolerance
3.0 - 20.0	+0.00/-0.10

